



MATERIAL SAFETY DATA SHEET

Substance key: 000000476725
Version : 1 - 1 / CDN

Revision Date: 11/28/2014
Date of printing :08/05/2015

WHMIS controlled: yes
Class: B2
D2A
D2B

Section 01 - Product and company identification

Identification of the company:

Clariant (Canada) Inc.
2 Lone Oak Court
Toronto, Ontario, M9C 5R9
Telephone No.: +1 514-832-2559

Information of the substance/preparation:

ESHA
Phone (514) 832 2559, Fax (704) 330 1505
Canada.PS@Clariant.com

Emergency tel. number: +1 800-424-9300 CHEMTREC, +1 (703) 527-3887 INTERNATIONAL

Trade name: CORRTREAT 700
Material number: 252584

Primary product use: Corrosion inhibitor

Section 02 - Hazards identification

Health effects of exposure:

Flammable. Toxic by ingestion and skin absorption. Harmful by inhalation. Contact with eyes will cause severe irritation and may cause burns and permanent damage. Contact with skin will cause severe irritation and may cause burns. Inhalation of vapours, spray or aerosols will cause irritation to the respiratory system and may cause lung damage. May affect fetal development.

Xylene (o,m,p- isomers): are reported as teratogenic and reproductive effectors in rodents. The substance is toxic to blood, kidneys, the nervous system, liver. Repeated or prolonged exposure can cause cumulative effects in target organs. Inhalation of high concentrations may cause irritation of the nose and throat and signs of nervous system depression (headache, fatigue, dizziness and drowsiness).

Section 03 - Composition/information on ingredients

Hazardous ingredients:

Component	CAS number	Concentration
Xylene	1330-20-7	40 - 70 %
Ethylbenzene	100-41-4	10 - 30 %

Component toxicity information:

Xylene (1330-20-7)

Substance key: 00000476725
Version : 1 - 1 / CDN

Revision Date: 11/28/2014
Date of printing :08/05/2015

Acute oral toxicity: LD50 4,300 mg/kg (Rat)

Section 04 - First aid measures

After inhalation:

Move the victim to fresh air.
Give oxygen or artificial respiration if needed.
Get immediate medical advice/ attention.
Never give anything by mouth to an unconscious person.

After contact with skin:

Remove contaminated clothing and wash affected areas with soap and plenty of water for at least 15 minutes. If redness or skin irritation occurs, seek medical attention.

After contact with eyes:

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

After ingestion:

If swallowed, DO NOT induce vomiting.
Get immediate medical advice/ attention.

Advice to doctor / Treatment:

None known.

Section 05 - Fire fighting measures

Flashpoint: 24 °C

Extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special fire fighting procedure:

Wear full protective clothing and self-contained breathing apparatus.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool endangered containers with water spray jet.

Hazardous combustion products:

In case of fire hazardous decomposition products may be produced such as:
Carbon oxides
Nitrogen oxides (NOx)
Container explosion may occur under fire conditions.

Section 06 - Accidental release measures

Substance key: 000000476725
Version : 1 - 1 / CDN

Revision Date: 11/28/2014
Date of printing :08/05/2015

Steps to be taken in case of spill or leak:

Only trained personnel should be involved in spill operations. Wear suitable protective equipment. Ensure adequate ventilation. Remove all ignition sources. Contain spill and pump into proper containers using explosion-proof equipment. Smaller spills may be recovered using an inert non-combustible absorbent material (sand, kieselguhr) and collected into suitable containers. Do not use organic absorbent material. Containers in which spilt substance has been collected must be properly labelled. Spill may be covered with an appropriate foam to hinder the formation of explosive vapours. Wash spill area. Do not allow to enter sewers, storm drains, surface waters or the soil.

Section 07 - Handling and storage**Advice on safe handling:**

Keep away from heat, sparks and open flames. - Avoid breathing vapors or contact with skin, eyes, and clothing.- Use only with adequate ventilation and proper protective eyewear, face shield, gloves and clothing. Wash thoroughly after handling. Keep container closed.

Further info on storage conditions:

Keep containers tightly closed in a cool, well-ventilated place.
Handle and open container with care.
Keep away sources of ignition.

Section 08 - Exposure controls / personal protection**Occupational exposure limits:**

Component	CAS number:	Regulatory list	Type of value	Value 1	Value 2
Xylene (o, m & p isomers)	1330-20-7	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	100 ppm	
Xylene (o, m & p isomers)	1330-20-7	USA. ACGIH Threshold Limit Values (TLV)	Short-term exposure limit	150 ppm	
Xylene (o, m & p isomers)	1330-20-7	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	100 ppm	
Xylene (o, m & p isomers)	1330-20-7	USA. ACGIH Threshold Limit Values (TLV)	Short-term exposure limit	150 ppm	
Ethyl benzene	100-41-4	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	20 ppm	
Ethyl benzene	100-41-4	USA. ACGIH Threshold Limit Values (TLV)	Short-term exposure limit	125 ppm	

Respiratory protection:

Wear an approved respirator when exposed to vapours or to mists beyond the TLV. Use appropriate filters. Do not exceed filters limitations. TLV = Threshold Limit Value

Hand protection:

Butyl Rubber, PVC or Neoprene

Eye protection:

Safety goggles
Face-shield

Substance key: 00000476725
Version : 1 - 1 / CDN

Revision Date: 11/28/2014
Date of printing :08/05/2015

Other protective equipment: Avoid skin contact.
Wear suitable protective clothing.

Section 09 - Physical and chemical properties

Form: Liquid
Color: dark amber
pH: Not applicable
Density: 0.880 - 0.920 g/cm³

Section 10 - Stability and reactivity

Chemical stability: Stable
Hazardous Polymerization: no
Conditions to avoid: None known.
**Incompatibility with
(Conditions to avoid) :** Keep away from heat.
Keep away from flames and sparks.

Section 11 - Toxicological information

Acute oral toxicity: The product has not been tested. The information is derived from the properties of the individual components., Toxic by inhalation and if swallowed.
Acute dermal toxicity: The product has not been tested. The information is derived from the properties of the individual components.
Skin irritation: Severe skin irritation
The product has not been tested. The information is derived from the properties of the individual components.
Eye irritation: Risk of serious damage to eyes.
The product has not been tested. The information is derived from the properties of the individual components.

Section 12 - Ecological information

Product information:

Remarks:

The product should not be allowed to enter drains, water courses or the soil.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Section 13 - Disposal considerations

Substance key: 000000476725
Version : 1 - 1 / CDN

Revision Date: 11/28/2014
Date of printing :08/05/2015

Waste disposal information:

Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities.

Section 14 - Transport information**TDG**

Proper shipping name: Flammable liquid, n.o.s.
Class: 3
Packing group: III
UN/ID number: UN 1993
Primary risk: 3
Remarks: Shipment permitted
Hazard inducer(s): Xylene

IATA

Proper shipping name: Flammable liquid, n.o.s.
Class: 3
Packing group: III
UN/ID number: UN 1993
Primary risk: 3
Remarks: Shipment permitted
Hazard inducer(s): Xylene

IMDG

Proper shipping name: Flammable liquid, n.o.s.
Class: 3
Packing group: III
UN no.: UN 1993
Primary risk: 3
Hazard inducer(s): Xylene
EmS: F-E S-E

Section 15 - Regulatory information**Registration status**

DSL: yes
NDSL: no

CEPA

Listed as toxic substance: Not listed
Listed as priority substance: Listed

NPRI

Listed

Section 16 - Other information

Substance key: 00000476725
Version : 1 - 1 / CDN

Revision Date: 11/28/2014
Date of printing :08/05/2015

WHMIS



Flammable
Toxic by ingestion
Harmful by inhalation and in contact with skin.

The information contained on this MSDS is to the best of our knowledge an accurate summary of the data available as of the date of preparation. Clariant (Canada) Inc. is not liable for the application or use of this information in situations beyond its control or outside the normal and expected use of its product. Clariant (Canada) Inc. assumes no responsibility for damage or injury from the use of the product described herein.