



Substance key: 000000467415

Revision Date: 11/28/2014

Version : 1 - 1 / CDN

Date of printing :02/21/2015

WHMIS controlled: yes
Class: B2
 D 2 A
 D 2 B

Section 01 - Product and company identification

Identification of the company: Clariant (Canada) Inc.
 2 Lone Oak Court
 Toronto, Ontario, M9C 5R9
 Telephone No.: +1 514-832-2559

Information of the substance/preparation:

ESHA
 Phone (514) 832 2559, Fax (704) 330 1505
Canada.PS@Clariant.com

Emergency tel. number: +1 800-424-9300 CHEMTREC, +1 (703) 527-3887 INTERNATIONAL

Trade name: **MULTITREAT 13227**
Material number: 280988

Primary product use: Packer Fluid Inhibitor

Section 02 - Hazards identification

Health effects of exposure:

Flammable. Toxic by ingestion, inhalation and skin contact. Irritant to skin and eyes. May affect fetal development.

Methanol: toxic by ingestion, inhalation and skin contact. Danger of very serious irreversible effects through ingestion, inhalation and skin contact including blindness. Highly flammable. Teratogen.

Ethylene glycol : human poison by ingestion. Very toxic by inhalation. A skin, eye and mucous membrane irritant. Human systemic effect by ingestion and inhalation (eye lacrimation, general anesthesia, head- ache, cough, respiratory stimulation, nausea or vomiting, pulmonary, kidney and liver changes). There is evidence of experimental terato- genic and mutagenic data. Repeated or high exposure may cause kidney and brain damage.

Section 03 - Composition/information on ingredients

Hazardous ingredients:

Component	CAS number	Concentration
Methyl alcohol	67-56-1	7 - 13 %
Ethylene glycol	107-21-1	1 - 5 %

Component toxicity information:

Ethylene glycol (107-21-1)

Substance key: 000000467415Revision Date: 11/28/2014

Version : 1 - 1 / CDN

Date of printing :02/21/2015

Acute oral toxicity: LD50 4,700 mg/kg (Rat)

Section 04 - First aid measures

After inhalation:

Move the victim to fresh air.
Give oxygen or artificial respiration if needed.
Get immediate medical advice/ attention.
Never give anything by mouth to an unconscious person.

After contact with skin:

Remove contaminated clothing and wash affected areas with soap and plenty of water for at least 15 minutes. If redness or skin irritation occurs, seek medical attention.

After contact with eyes:

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

After ingestion:

If swallowed, DO NOT induce vomiting.
Get immediate medical advice/ attention.

Advice to doctor / Treatment:

None known.

Section 05 - Fire fighting measures

Flashpoint: 29 °C
Method: closed cup

Extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special fire fighting procedure:

Wear full protective clothing and self-contained breathing apparatus.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool endangered containers with water spray jet.

Hazardous combustion products:

In case of fire hazardous decomposition products may be produced such as:
Carbon oxides
Nitrogen oxides (NO_x)
Container explosion may occur under fire conditions.

Section 06 - Accidental release measures

Steps to be taken in case of spill or leak:

Wear prescribed protective equipment. Eliminate all ignition sources. Contain spill. Use explosion-proof equipment to ventilate the area and to pump the spill into appropriate containers. Smaller spill may be recovered by using an inert absorbent. May cover the spill with appropriate foam to hinder the formation of explosive vapors. Wash the spill area.

Section 07 - Handling and storage

Substance key: 000000467415

Revision Date: 11/28/2014

Version : 1 - 1 / CDN

Date of printing :02/21/2015

Advice on safe handling:

Keep away from heat, sparks and open flames. - Avoid breathing vapors or contact with skin, eyes, and clothing.- Use only with adequate ventilation and proper protective eyewear, face shield, gloves and clothing. Wash thoroughly after handling. Keep container closed.

Further info on storage conditions:

Keep containers tightly closed in a cool, well-ventilated place.
Handle and open container with care.
Keep away sources of ignition.

Section 08 - Exposure controls / personal protection**Occupational exposure limits:**

Component	CAS number	Regulatory list	Type of value	Value 1	Value 2
Methanol	67-56-1	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	200 ppm	
Methanol	67-56-1	USA. ACGIH Threshold Limit Values (TLV)	Short-term exposure limit	250 ppm	
Ethylene glycol (Aerosol)	107-21-1	USA. ACGIH Threshold Limit Values (TLV)	Ceiling limit		100 mg/m3
Ethylene glycol	107-21-1	USA. ACGIH Threshold Limit Values (TLV)	Ceiling limit		100 mg/m3

Respiratory protection:

Wear an approved respirator when exposed to vapours or to mists beyond the TLV. Use appropriate filters. Do not exceed filters limitations. TLV = Threshold Limit Value

Hand protection:

Butyl Rubber, PVC or Neoprene

Eye protection:

Safety goggles
Face-shield

Other protective equipment:

Avoid skin contact.
Wear suitable protective clothing.

Section 09 - Physical and chemical properties

Form:	Liquid
Color:	clear
Color:	dark amber
Odor:	pungent
pH:	6 - 8
Solubility in water:	completely soluble
Density:	1.13 - 1.145 g/cm ³ (25 °C)
Freezing point :	-40 °C

Substance key: 000000467415
Version : 1 -1 / CDN

Revision Date: 11/28/2014
Date of printing :02/21/2015

Section 10 - Stability and reactivity

Chemical stability: Stable

Hazardous Polymerization: no
Conditions to avoid: None known.

**Incompatibility with
(Conditions to avoid) :** Keep away from heat.
Keep away from flames and sparks.

Section 11 - Toxicological information

Skin irritation: irritating
The product has not been tested. The information is derived from the properties of the individual components.

Eye irritation: irritating
The product has not been tested. The information is derived from the properties of the individual components.

Section 12 - Ecological information

Product information:

Remarks:

The product should not be allowed to enter drains, water courses or the soil.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Section 13 - Disposal considerations

Waste disposal information:

Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities.

Section 14 - Transport information

TDG

Proper shipping name: Flammable liquid, n.o.s.
Class: 3
Packing group: III
UN/ID number: UN 1993
Primary risk: 3
Remarks: Shipment permitted
Hazard inducer(s): Methanol

IATA

Proper shipping name: Flammable liquid, n.o.s.
Class: 3
Packing group: III
UN/ID number: UN 1993
Primary risk: 3

Substance key: 000000467415

Revision Date: 11/28/2014

Version : 1 -1 / CDN

Date of printing :02/21/2015

Remarks: Shipment permitted
Hazard inducer(s): Methanol

IMDG

Proper shipping name: Flammable liquid, n.o.s.
Class: 3
Packing group: III
UN no.: UN 1993
Primary risk: 3
Hazard inducer(s): Methanol
EmS: F-E S-E

Section 15 - Regulatory information**Registration status**

DSL: yes
NDSL: no

CEPA

Listed as toxic substance: Not listed
Listed as priority substance: Listed

NPRI**Listed****Section 16 - Other information****WHMIS**

Flammable
Causes eye, skin, and respiratory tract irritation.
Harmful if swallowed.
MAY CAUSE BIRTH DEFECTS BASED ON ANIMAL DATA

The information contained on this MSDS is to the best of our knowledge an accurate summary of the data available as of the date of preparation. Clariant (Canada) Inc. is not liable for the application or use of this information in situations beyond its control or outside the normal and expected use of its product. Clariant (Canada) Inc. assumes no responsibility for damage or injury from the use of the product described herein.