

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: Diversity Technologies Corp. DATE: January 12, 2017

8750 – 53rd Ave. PHONE: **780-440-4923 Edmonton, AB T6E 5G2** FAX: **780-469-1899**

PRODUCT NAME: Grout-Well and Grout-Well DF

PRODUCT USE: Oilwell drilling fluid additive.

CHEMICAL FAMILY: Montmorillonite CAS #: 1302-78-9

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D2A

WORKPLACE HAZARD: Potential carcinogen; contains free silica.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG

TDG CLASSIFICATION: Not applicable UN NUMBER (PIN): Not applicable PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	% (w/w)	CAS NUMBER	LD ₅₀ Oral-Rat	LC ₅₀ Inhal-Rat	ACGIH-TLV
Silica, crystalline	1-5 or	14808-60-7	Not available	Not available	0.025 mg/m^3
quartz	5-10*				(respirable)

*The typical quartz content of western bentonite is between 2 and 6%.

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: □ EYE CONTACT □ SKIN CONTACT ☑ INHALATION □ INGESTION

EYE CONTACT: May cause mechanical irritation.

SKIN CONTACT: Possible drying resulting in dermatitis.

INGESTION: No adverse effects expected.

INHALATION: May cause irritation of the upper respiratory tract. This product contains

crystalline silica. Breathing silica containing dust may not cause

noticeable injury or illness even though permanent lung damage may be occurring. Chronic inhalation may cause silicosis, a progressive, disabling

and sometimes fatal lung disease. Chronic inhalation exposure to

crystalline silica quartz has been observed to cause lymph node effects,

kidney effects and auto-immune disease.

GROUT-WELL AND GROUT-WELL DF

CARCINOGENICITY: Bentonite is not listed by ACGIH, IARC, NTP or OSHA. Crystalline silica,

when inhaled from occupational sources, is considered as a human carcinogen by IARC (Class 1) and by NTP. ACGIH classifies crystalline

silica, quartz, as a suspected human carcinogen (A2).

TERATOGENICITY: No information available. REPRODUCTIVE TOXICITY: No information available.

MUTAGENICITY: Crystalline silica has been shown to cause mutagenic effects in human

cells in-vitro.

SYNERGISTIC PRODUCTS: No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: If irritation occurs, or when shift ends, wash with soap and water until

clean.

EYE CONTACT: Flush with water until irritation ceases. If irritation persists, contact a

physician.

INGESTION: No first aid required; material is non-toxic.

INHALATION: Move to area free from dust. If symptoms or irritation persist contact a

physician. Inhalation may aggravate existing respiratory illness.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR: Light tan to gray powder or granules; odourless

SPECIFIC GRAVITY: 2.45 – 2.55 BOILING POINT ($^{\circ}$ C): Not applicable MELTING POINT ($^{\circ}$ C): \sim 1450

MILLITING POINT (C).

SOLUBILITY IN WATER: Insoluble pH: 8 – 10 (5% aq. sol'n)

PERCENT VOLATILE BY VOLUME:

EVAPORATION RATE:

VAPOUR PRESSURE (mmHg):

VAPOUR DENSITY (air = 1):

BULK DENSITY:

Not applicable

Not applicable

Not applicable

49 - 70 lbs/ft³

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Not applicable FLAMMABLE LIMITS: Not applicable

EXTINGUISHING MEDIA: Use media suitable for surrounding fire and

packaging.

SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus required for fire-

fighting personnel.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Product becomes very slippery when wet, avoid using

water as firefighting agent.

HAZARDOUS COMBUSTION PRODUCTS: No information available.

GROUT-WELL AND GROUT-WELL DF

SECTION VII: REACTIVITY DATA

STABILITY:

STABLE UNSTABLE

INCOMPATIBILITY (CONDITIONS TO AVOID): None known. Avoid contact with hydrofluoric acid.

CONDITIONS OF REACTIVITY: Not available. HAZARDOUS DECOMPOSITION PRODUCTS: None known.

HAZARDOUS POLYMERIZATION:
☑ WILL NOT OCCUR
☐ MAY OCCUR

SECTION VIII: PREVENTIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH/MESA approved respirators for silica bearing

dust.

VENTILATION: Use local exhaust ventilation, process enclosure or

other engineering controls to maintain concentration

of airborne dust below TLV.

PROTECTIVE GLOVES: Generally not necessary; personal preference.

EYE PROTECTION: Suggest goggles or safety glasses.

OTHER PROTECTIVE EQUIPMENT (SPECIFY): Ensure emergency eye wash station and safety

shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid creating dust. Avoid breathing dust; wear an approved respirator. Practice reasonable caution and personal cleanliness. Avoid eye contact. Store in cool, dry area. Empty packages contain residual hazardous material; handle as if full.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Wear an approved respirator. Vacuum if possible to avoid generating airborne dust. Collect uncontaminated material for repackaging. Collect contaminated material in an approved container for disposal. Avoid adding water; the product will become slippery when wet.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the enduser to determine if material meets the criteria of hazardous waste at the time of disposal. Empty packaging must be disposed of, or recycled, in accordance with local regulations.

GROUT-WELL AND GROUT-WELL DF

SECTION IX: PREPARATION

The information contains herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED:

SUPERSEDES:

BY:

PHONE:

January 12, 2017

January 14, 2014

Regulatory Affairs

780-440-4923