

Substance key: 000000464347  
 Version : 1 -1 / CDN

Revision Date: 11/28/2014  
 Date of printing :02/04/2015

**WHMIS controlled:** yes  
**Class:** B2  
 D 1 B  
 D 2 A  
 D 2 B

**Section 01 - Product and company identification**

**Identification of the company:** Prairie Mud Service  
 738 6th Street, Estevan, Sk. S4A 1A4  
 306-634-3411

**Supplier:** Prairie Petro Chem of America  
 3119 1st Ave W, Williston, ND. 58801  
 701-774-2436

**Primary product use:** Hydrogen sulfide scavenger

**Section 02 - Hazards identification**

**Health effects of exposure:**

Flammable. Toxic by ingestion. Harmful by inhalation and skin contact. Eye and skin contact will cause burns. Inhalation of spray or mists will cause burns to the respiratory tract. May result in permanent damage. May affect fetal development.  
 Methanol: toxic by ingestion, inhalation and skin contact. Danger of very serious irreversible effects through ingestion, inhalation and skin contact including blindness. Highly flammable. Teratogen.  
 Monoethanolamine: harmful by ingestion and inhalation. Eye and skin contact will cause burns. Inhalation of spray or mists will cause burns to the respiratory tract. May result in permanent damage. May cause liver and kidney damage. May damage the developing fetus.

**Section 03 - Composition/information on ingredients**

**Hazardous ingredients:**

Component	CAS number	Concentration
Alkanolamine/Aldehyde condensate		60 - 100 %
Methyl alcohol	67-56-1	10 - 30 %
Monoethanolamine	141-43-5	1 - 5 %

---

Substance key: 000000464347

Revision Date: 11/28/2014

Version : 1 - 1 / CDN

Date of printing :02/04/2015

---

### Component toxicity information:

Methyl alcohol ( 67-56-1 )

**Acute oral toxicity:** LDO 428 mg/kg (Humans)

Monoethanolamine ( 141-43-5 )

**Acute oral toxicity:** LD50 2,140 mg/kg (Rat)

## Section 04 - First aid measures

### After inhalation:

Get victim to fresh air. Loosen tight clothing such as collar, tie, belt or waistband. If breathing is difficult administer oxygen. If victim is not breathing, give mouth to mouth resuscitation.

Get prompt medical attention. Warning: giving mouth to mouth resuscitation when the inhaled material is toxic may be hazardous to the person providing aid.

### After contact with skin:

Remove contaminated clothing and wash affected areas with plenty of water. Get immediate medical assistance for treatment of burns.

### After contact with eyes:

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

### After ingestion:

If swallowed, DO NOT induce vomiting.  
Get immediate medical advice/ attention.

### Advice to doctor / Treatment:

None known.

## Section 05 - Fire fighting measures

### Flashpoint:

> 93 °C

Method: Pensky-Martens (DIN EN ISO 2719) (closed cup)

### Ignition temperature:

not tested.

### Extinguishing media:

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### Special fire fighting procedure:

Wear full protective clothing and self-contained breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Cool endangered containers with water spray jet.

### Hazardous combustion products:

In case of fire hazardous decomposition products may be produced such as:

Carbon oxides

Nitrogen oxides (NOx)

Container explosion may occur under fire conditions.

## Section 06 - Accidental release measures

# MATERIAL SAFETY DATA SHEET

## H2S Scavenger

Page 3 of 6

Substance key: 000000464347

Revision Date: 11/28/2014

Version : 1 - 1 / CDN

Date of printing :02/04/2015

### Steps to be taken in case of spill or leak:

Only trained personnel should be involved in spill operations. Wear suitable protective equipment. Ensure adequate ventilation. Remove all ignition sources. Contain spill and pump into proper containers using explosion-proof equipment. Smaller spills may be recovered using an inert non-combustible absorbent material (sand, kieselguhr) and collected into suitable containers. Do not use organic absorbent material. Containers in which spilt substance has been collected must be properly labelled. Spill may be covered with an appropriate foam to hinder the formation of explosive vapours. Wash spill area. Do not allow to enter sewers, storm drains, surface waters or the soil.

## Section 07 - Handling and storage

### Advice on safe handling:

Keep away from heat, sparks and open flames. - Avoid breathing vapors or contact with skin, eyes, and clothing.- Use only with adequate ventilation and proper protective eyewear, face shield, gloves and clothing. Wash thoroughly after handling. Keep container closed.

### Further info on storage conditions:

Keep containers tightly closed in a cool, well-ventilated place.  
Handle and open container with care.  
Keep away sources of ignition.

## Section 08 - Exposure controls / personal protection

### Occupational exposure limits:

Component	CAS number:	Regulatory list	Type of value	Value 1	Value 2
Methanol	67-56-1	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	200 ppm	
Methanol	67-56-1	USA. ACGIH Threshold Limit Values (TLV)	Short-term exposure limit	250 ppm	

### Respiratory protection:

Wear an approved respirator when exposed to vapours or to mists beyond the TLV. Use appropriate filters. Do not exceed filters limitations. TLV = Threshold Limit Value

### Hand protection:

Butyl Rubber, PVC or Neoprene

### Eye protection:

Safety goggles  
Face-shield

### Other protective equipment:

Avoid skin contact.  
Wear suitable protective clothing.

## Section 09 - Physical and chemical properties

**Form:** Liquid  
**Color:** light yellow  
**Odor limit:** not tested.  
**pH:** 10 - 11

# MATERIAL SAFETY DATA SHEET

## H2S Scavenger

Page 4 of 6

Substance key: 000000464347

Revision Date: 11/28/2014

Version : 1 - 1 / CDN

Date of printing :02/04/2015

**Solubility in water:** completely **soluble**  
**Density:** **1.035** - 1.05 g/cm<sup>3</sup> (20 °C)  
**Freezing point :** < -34 °C

### Section 10 - Stability and reactivity ]

**Thermal decomposition:** No decomposition if used as directed.  
**Chemical stability:** Stable  
**Hazardous Polymerization:** no  
Conditions to avoid: Strong oxidizing agents  
**Incompatibility with (Conditions to avoid) :** Keep away from heat and flames. Avoid contact with oxidizing materials.  
**Hazardous decomposition products** Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide and carbon dioxide

### Section 11 - Toxicological information

**Acute oral toxicity:** May be harmful if swallowed., Data relate to methanol  
**Skin irritation:** irritating  
Information refers to the main component.  
**Eye irritation:** irritating  
Information refers to the main component.

### Section 12 - Ecological information

#### Product information:

#### Remarks:

The product should not be allowed to enter drains, water courses or the soil.  
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Component information:

Methanol ( 67-56-1 )

**Biodegradation:** **99 %** (28 d)  
Method: OECD Test Guideline 301D  
**Fish toxicity:** LC50 19,000 mg/l (96 h, Oncorhynchus mykiss (rainbow trout))  
**Daphnia toxicity:** LC50 > 10,000 mg/l (24 h)  
**Bacteria toxicity:** IC50 > 1,000 mg/l (3 h, activated sludge)

### Section 13 - Disposal considerations

# MATERIAL SAFETY DATA SHEET

## H2S Scavenger

Page 5 of 6

Substance key: 000000464347

Revision Date: 11/28/2014

Version : 1 - 1 / CDN

Date of printing :02/04/2015

### Waste disposal information:

Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities.

## Section 14 - Transport information

### TDG

Proper shipping name: Flammable liquid, n.o.s.  
Class: 3  
Packing group: III  
UN/ID number: UN 1993  
Primary risk: 3  
Remarks: Shipment permitted  
Hazard inducer(s): Methanol

### IATA

Proper shipping name: Flammable liquid, n.o.s.  
Class: 3  
Packing group: III  
UN/ID number: UN 1993  
Primary risk: 3  
Remarks: Shipment permitted  
Hazard inducer(s): Methanol

### IMDG

Proper shipping name: Flammable liquid, n.o.s.  
Class: 3  
Packing group: III  
UN no.: UN 1993  
Primary risk: 3  
Hazard inducer(s): Methanol  
EmS: F-E S-E

## Section 15 - Regulatory information

### Registration status

DSL: yes  
NDSL: no

### CEPA

Listed as toxic substance: Not listed  
Listed as priority substance: Not listed

### NPRI

Listed

### TSCA Status:

All components of this product are listed on the TSCA Inventory.

## Section 16 - Other information

# MATERIAL SAFETY DATA SHEET

## H2S Scavenger

Page 6 of 6

---

Substance key: 000000464347  
Version : 1 - 1 / CDN

Revision Date: 11/28/2014  
Date of printing :02/04/2015

---

### WHMIS



Flammable  
Toxic if swallowed.  
Harmful by inhalation and in contact with skin.

---

The information contained on this MSDS is to the best of our knowledge an accurate summary of the data available as of the date of preparation. Prairie Mud Service is not liable for the application or use of this information in situations beyond its control or outside the normal and expected use of its product. Prairie Mud Service assumes no responsibility for damage or injury from the use of the product described herein.